



TPED DISPOSABLE ALUMINUM CYLINDER



200118017

Material: High Strength Aluminum Alloy AA6061-T6.

Standard: ISO 11118 standard/TPED; ISO9001.

Suitable Gas: CO₂, O₂, AR, N₂, HE, Mixed Gas.

Cylinder Threads: M14×1.5 Outlet

Finish: Polished or color coated

Cleaning: Commercial cleaning for normal gas and specific cleaning for specialty gas.

Approval Body: TÜV Rheinland

Aluminum Advantage: Corrosion-resistant interior and exterior, Light weight.

Graphics: logos or labels in screen print, shrink sleeves, and sticker are available.

Accessories: Valves can be installed upon request.

SPECIFICATIONS

TYPE	VOLUME (L)	WORK PRESSURE (bar)	DIAMETER (mm)	HEIGHT (mm)	WEIGHT (kg)	CO ₂ (kg)	O ₂ (L)
TPED-70-110-0.2L	0.2	110	70	115	0.25	0.13	22
TPED-70-110-0.3L	0.3	110	70	145	0.30	0.19	33
TPED-70-110-0.42L	0.42	110	70	185	0.37	0.26	46.2
TPED-70-110-0.5L	0.5	110	70	210	0.41	0.31	55
TPED-70-110-0.68L	0.68	110	70	265	0.51	0.43	74.8
TPED-70-110-0.8L	0.8	110	70	300	0.57	0.50	88
TPED-70-110-0.95L	0.95	110	70	350	0.65	0.59	104.5
TPED-70-110-1L	1.0	110	70	365	0.67	0.63	110
TPED-70-110-1.1L	1.1	110	70	395	0.73	0.66	115.5

* Custom sizes are also available