



## TPED INDUSTRIAL GAS ALUMINUM CYLINDER



**Service Pressure:** 166.7bar

**Standard:** ISO 7866 designed, TPED  $\pi$  Certification

**Material:** AA 6061

**Threads:** 0.4L-1.5L with M18×1.5/17E, 2L or larger with 25E

**Finish:** Standard finish is brushed body with unpainted crown;  
Heat sensitive clear coat is available upon request.

**Graphics:** Logos and labels available upon request.

**Cleaning:** Commercially cleaned & specialty gas cleaned.

**Accessories:** Valves can be installed upon request. 13.4L  
available with handle, cap & collar available upon request.

## SPECIFICATIONS

TYPE #	WATER CAPACITY	DIAMETER	LENGTH	CYLINDER WEIGHT	CO2	NITROGEN
	liters					
TPED-60-0.4L	0.4	60	245	0.48	0.30	65.8
TPED-70-0.5L	0.5	70	230	0.63	0.38	82.3
TPED-70-0.8L	0.8	70	332	0.85	0.60	131.6
TPED-89-1L	1	89	268	1.15	0.75	164.5
TPED-89-1.5L	1.5	89	372	1.58	1.13	246.8
TPED-111-2L	2	111	352	2.34	1.50	329.0
TPED-111-2.7L	2.67	111	442	2.83	2.00	439.3
TPED-111-3L	3	111	488	3.07	2.25	493.6
TPED-140-5L	5	140	518	5.30	3.75	822.6
TPED-203-13.4L	13.4	203	636	14.22	10.05	2204.6

\*Custom sizes are also available