



TPED SCUBA ALUMINUM CYLINDER



Service Pressure: 200 bar

Standard: ISO 7866 designed, TPED π Certification

Material: AA 6061

Threads: 0.5L with M18×1.5/17E, all others with M25×2

Finish: Shot blaster, fully brushed & powder coat finishes available.

Graphics: Logos and labels available upon request.

Cleaning: Commercially cleaned & specialty gas cleaned.

Accessories: Valves installed upon request. 7L or larger available with handle, cap & collar available upon request.

SPECIFICATIONS

TYPE #	AIR CAPACITY	WATER CAPACITY	DIAMETER	LENGTH	WEIGHT	BUOYANCY		
	liters	liters				mm	mm	kgs
TPED-70-0.5L	99	0.5	70	243	0.75	-0.1	0.0	0.03
TPED-111-2L	395	2	111	359	2.80	-0.3	0.0	0.24
TPED-111-3L	592	3	111	500	3.77	-0.2	0.2	0.63
TPED-140-5L	987	5	140	558	6.67	-0.5	0.2	0.80
TPED-140-7L	1382	7	140	716	8.38	-0.2	0.8	1.72
TPED-175-10L	1974	10	175	668	12.83	-0.8	0.6	1.92

*Custom sizes are also available